www.rinaldin.com

MEASURING and CUTTING

RINALDIN	MEASURING and CUTTING ww										w.m	naic	din.com	
ILLUSTRATION	DESCRIPTION				PRICE				Disc.	3° Disc. 4° Disc.				Code
		Snap-off knife with st	teel slide.		1,80	Q.ty	20%	Q.ty	30%	Q.ty	40%	Q.ty 60	45%	2312
	mm 9	Small size. Snap-off blades small size for knife 2312.		,			20	30%	50	40%		45%	233P	
		Thickness 0,4 mm. Width 9 mm. Box 10 blades. Snap-off knife with steel slide.			1,30	4	20%					100		
	mm 18	Medium size.			2,70	4	20%	10	30%	30	40%	60	45%	2311
		Snap-off blades medium size for knife 2311. Thickness 0,5 mm. Width 18 mm. Box 10 blades.		2,25	4	20%	20	30%	30	40%	100	45%	233G	
		Snap-off knife with steel slide. Large size.		4,60	4	10%	10	20%	30	30%	60	35%	2310	
	mm 25	Snap-off blades large size for knife 2310. Thickness 0,6 mm. Width 25 mm. Box 10 blades.		3,00	4	20%	20	30%	50	40%	100	45%	233X	
Video on Rinaldin website	1	Logan 500 Cutter. Cuts mount boards at 90°. It is possible				_								
		to adjust the depth of the blade.		12,00	3		10	12%					L500	
		Spare blades for Logan 500 Box 100 blades Box 100 blades		4,80 21,00	3 3	10% 10%	10 10	15% 15%					L270 L270C	
		Professional fixed blade knife. You do not need open the knife to insert or take off the blade. Just push the black spring to adjust the blade. Tank incorporating a reserve blades. 3 blades supplied.		17,20	3	6%	10	10%					238	
		Big trapezoidal blades. 0.65 mm thick. 60 mm long. Suitable for knife 237 and 238. Box of 5 blades.			0,95	5	20%	24	30%	48	40%	96	45%	238G
		Free-hand knife for precision cutting. For photographers and graphics. 5 blades supplied.			3,30	4	20%	12	30%	24	40%	48	45%	AK2
		Blades for knife AK2. Box of 5 blades.		0,95	5	20%	20	30%	50	40%	100	45%	AK2L	
0		Wheel cutter. Particularly useful for cutting fabrics, leather, plastics and paper.		4,30	4	10%	12	20%	24	30%	48	35%	236	
		Blade diameter 45 mm. 2 blades included. Spare blades for wheel cutter		1,50	5	20%	20	30%	60	40%	120	45%	236L	
		Compass cutter to cu	Compass cutter to cut paperboard.		Ĺ									
Allent Bur		Maximum diameter 150 mm. 6 spare blades and 2 graphite points included. Spare blades for compass cutter. In the pack 12 blades and 2 graphite points.		included.	2,50	4	20%	12	30%	24	40%	48	45%	239
				1,60	6	20%	12	30%	36	40%	72	45%	239L	
	Retractable measuring	2 metres. Tape 13 mm wide			3,20	4	10%	10	15%					2212
	tape with stop and automatic re-entry.	3 metres. Tape 16 r	ane 16 mm wide			4	10%	10	15%					2213
mm 0,1 PVC	Cutting Mat				4,80						05		20	00000
mm 0,9 PVC soft mm 1 PVC hard		e as blades can penetra	enetrate	cm 22x30	3,80	3	10%	10	20%	30	25%	60	28%	22830
mm 0,9 PVC soft mm 0,1 PVC	without breaking or blunt The cutting mat will rema	ain smooth with an u	h an unlimited	cm 30x45	7,30	3	10%	10	20%	30	25%	60	28%	22845
	number of cuts (to avoid inclined cumountboards). White alignment grid on one side to hel operations. The mat is 3 mm thick and can be		tting on cm											
				cm 45x60	13,80	3	10%	10	20%	30	25%	60	28%	22860
	both sides. It is compose	of 5 layers of PVC.		cm 60x90	29,00	3	10%	10	20%	30	25%	60	28%	22890
		position could become wavy. placed next to a heat source												
	or heat of the sun.	pracea	cm 90x1		77,00	3	10%	10	20%	30	25%	60	28%	228120
	Aluminum safety rule.			cm 100	49,00	3	6%	10	10%					2292
	It has an ergonomically de-	signed handle profi	ile to protect	cm 150	72,00	3		10	10%					2293
	hands and a rubber strip for table.	perrect agnerence	0		96,00	3		10	10%					2294 2296
	A4 ()		cm 260		120,00	3	0%	10	10%					2290
· EAM	Metric aluminum rule "Channel Rail" by Logan with rubber. Suitable for all Logan cutters used for foamboard, as cutters can be attached to the rail. Length 81 cm.				42,00	3	8%	6	12%					W3001
The state of the s	Wooden folding rule. Length 2 metres.				3,00	4	15%							2222
	Stainless steel scissors. Blades length 12 cm. Produced by Stanley.				10,50	3	5%	6	10%					232
	German Löwe scissors for cutting slips and spacers at 45°.				58,00	3	6%							244
	Spare blade for Löwe scissors.			21,00	3	6%							244L	
	Cutter "Straight Cutter"													
	Cut straight 90° edges on any depth until 10 mm. Adjustable blade depth. Includes 5 blades.			34,00									WC6001	
The state of the s	Uses blades L492				7,00									7,00001
		toro MCC004	Pack 5 blade	s	3,50	3	10%							L492
mm 55 —	Blades for Logan mountcutt trapeizodal.	ers WC6001,	Pack 20 blades		12,50	3	10%							L492V
— mm 26 —	Blades for Mountcutter WB6	6020 (no longer	Pack 5 blades		3,40	3	10%							WB5
	in production).	uses (no longer	Pack 20 blades		13,50	3	10%							WB20
	Blades for Mountcutter WA8	3001 (no longer	Pack 5 blades		3,40	3	10%							WA5
mm 35	mm 35 in production).		Pack 20 blades		8,90	3	10%							WA20